

Nokrollen CR12-BR-IKO - CR12-BR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cr12-br-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) | D | C | d ₁ | G UNF | G ₁ | |
|-----------------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|-------------------------|--------------------------|--------------------------|--|---|--|--|
| | Shield type | | Sealed type | | | | | | | | |
| | With covered outer ring | With cylindrical outer ring | With covered outer ring | With cylindrical outer ring | g | | | | | | |
| 9.525 ($\frac{3}{8}$) | CR 12 | BR | | | 35 | 19.050 ($\frac{3}{4}$) | 12.700 ($\frac{1}{2}$) | 9.525 ($\frac{3}{8}$) | G ₁ -24 | 9.525 ($\frac{3}{8}$) | |
| Boundary dimensions mm/inch | | | | | | | | | | | |
| B mm | B ₂ | B ₃ | C ₁ | E ₁ | E ₂ | H | r | Bearing dimension f mm (mm/inch) | Maximum tightening torque C N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
| 14.2 (0.56) | 22.25 ($\frac{7}{8}$) | 6.350 ($\frac{1}{4}$) | 0.794 ($\frac{1}{16}$) | 4.762 ($\frac{3}{16}$) | 2.381 ($\frac{1}{8}$) | 4.762 ($\frac{3}{16}$) | 0.794 ($\frac{1}{16}$) | 13.494 ($\frac{1}{2}$) | 10.8 | 4 420 | 5 170 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3616060462404 |
| Binnendiameter | 9.525 mm |
| Binnendiameter | 3/8" inch |
| Buitendiameter | 19.05 mm |
| Buitendiameter | 3/4" inch |
| Dikte | 12.7 mm |
| Dikte | 1/2" inch |
| Gewicht | 35 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE