


Nokrollen CR32-R-IKO - CR32-R-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cr32-r-iko>



CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
22.225 (⁷ / ₁₆)	CR 32	R			615	50.800 (2)	31.750 (1 ¹ / ₂)	22.225 (⁷ / ₁₆)	⁷ / ₁₆ -14	25.400 (1)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	δ ₁	δ ₂	F	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
33.5 (1.32)	50.800 (2)	12.700 (¹ / ₂)	0.794 (⁵ / ₁₆)	4.762 (³ / ₁₆)	4.762 (³ / ₁₆)	1.588 (¹ / ₁₆)	37.506 (1 ⁹ / ₁₆)	192	32 500	69 900

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060463036
Binnendiameter	22.225 mm
Buitendiameter	50.8 mm
Dikte	31.75 mm
Gewicht	615 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE