


Nokrollen
CR14-VR-IKO - CR14-VR-IKO

https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cr14-vr-iko



CR14-VR

Identification number		Mass (Ref.)
Stud dia. mm (inch)	Shield type With covered With cylindrical outer ring With slotted outer ring	g D C d1 G UNF G1
9.525 (3/8)	CR 14 VR	47 22.225 12.700 9.525 1/4 9.525 1/4

Boundary dimensions mm (inch)							Mounting dimension f Min. mm (inch)	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C0 N
B max	B2	B3	C1	S1	S2	r				
14.2 (0.56)	22.225 (7/8)	8.350 (1/3)	0.794 (1/8)	4.762 (3/8)	2.381 (1/8)	0.794 (1/8)	15.081 (5/8)	10.8	8 710	12 300

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060463463
Binnendiameter	9.525 mm
Buitendiameter	22.225 mm
Dikte	12.7 mm
Gewicht	47 g
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE