


Nokrollen CR30-VBR-IKO - CR30-VBR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cr30-vbr-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
19.050 ($\frac{3}{4}$)	CR 30	VBR			418	47.625 ($1\frac{7}{8}$)	25.400 (1)	19.050 ($\frac{3}{4}$)	7-16	22.225 ($\frac{7}{8}$)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
25.8106	44.450 ($1\frac{3}{4}$)	11.112 ($\frac{7}{8}$)	0.794 ($\frac{1}{16}$)	4.792 ($\frac{3}{8}$)	3.969 ($\frac{5}{16}$)	7.938 ($\frac{5}{8}$)	1.588 ($\frac{1}{16}$)	32.543 ($1\frac{1}{8}$)	100	35 300	55 600

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060464132
Binnendiameter	19.05 mm
Buitendiameter	47.625 mm
Dikte	25.4 mm
Gewicht	418 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE