

Naalddaatslager AZ507014-IKO - AZ507014-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naalddaatslager/az507014-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings

| Shaft dia. mm | Identification number | | | | | | | |
|---------------|-----------------------|---------------|-----------------------|---------------|----------------|----------------|---------------|--|
| | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g | |
| 50 | AZ 507014 | 185 | AZK 50706 | 68 | WS 5070 | GS 5070 | 58.5 | |

| Boundary dimensions mm | | | | | | | | | | Standard mounting dimensions mm | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ |
|------------------------|----|----|----------------|----------------|----------------|---|--------------------|----------------|----------------|---------------------------------|---------------------|-----------------------------|---|---|
| d | D | T | d _c | D _c | D _w | B | r _s (1) | C ₁ | C ₂ | d _s Min. | D _s Max. | N | N | rpm |
| 50 | 70 | 14 | 50.05 | 69.5 | 6 | 4 | 0.6 | 54 | 67 | 67 | 54 | 43 300 | 148 000 | 5 000 |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3616060465986 |
| Binnendiameter | 50 mm |
| Buitendiameter | 70 mm |
| Dikte | 14 mm |
| Gewicht | 185 g |
| Verpakking | - |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE