


## Naaldtaatslager AZK12017518-IKO - AZK12017518-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldtaatslager/azk12017518-iko>

**IKO**

**THRUST BEARINGS**

Thrust Roller Bearings



Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
120	<b>AZ 12017542</b>	4 020	<b>AZK 12017518</b>	1 640	<b>WS 120175</b>	<b>GS 120175</b>		1 190

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>
d	D	T	d <sub>c</sub>	D <sub>c</sub>	D <sub>w</sub>	B	r <sub>s</sub> (1)	C <sub>1</sub>	C <sub>2</sub>	d <sub>4</sub> Min.	D <sub>4</sub> Max.	N	N	rpm
120	175	42	120.1	174.5	18	12	1.1	132	168	167	133	313 000	1 160 000	2 000

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060466228
Binnendiameter	120 mm
Buitendiameter	175 mm
Dikte	18 mm
Gewicht	1640 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE