

Naaldtaatslager

AZ11016040-IKO - AZ11016040-IKO

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldtaatslager/az11016040-iko

IKO

THRUST BEARINGS

Thrust Roller Bearings

Identification number							
Shaft dia. mm	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
110	AZ 11016040	3 220	AZK 11016017	1 320	WS 110160	GS 110160	950

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽²⁾	
d	D	T	d ₁	D ₁	B	r _{min} ⁽¹⁾	C ₁	C ₂	d ₁ Min.	D ₁ Max.	C	C ₀	N	
110	160	40	110.1	159.5	17	11.5	1.1	120	154	153	121	282 000	1 030 000	2 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r

⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060466440
Binnendiameter	110 mm
Buitendiameter	160 mm
Dikte	40 mm
Gewicht	3220 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE