


Naaldtaatslager AZ26034055-IKO - AZ26034055-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldtaatslager/az26034055-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
260	AZ 26034055	15 400	AZK 26034025	6 600	WS 260340	GS 260340	4 400

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d ₄ Min.	D ₄ Max.	N	N	rpm
260	340	55	260.15	339	25	15	2.1	278	328	326	279	739 000	3 510 000	1 000

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952487755
Binnendiameter	260 mm
Buitendiameter	340 mm
Dikte	55 mm
Gewicht	15400 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE