


Sluitring GS80115-IKO - GS80115-IKO

<https://www.123kogellager.nl/accessoires/ringen/sluitring/gs80115-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
80	AZ 8011528	1 060	AZK 8011511	370	WS 80115	GS 80115		345

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
80	115	28	80.05	114.5	11	8.5	1	88	110	109	88	122 000	427 000	3 000

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060466891
Binnendiameter	80 mm
Buitendiameter	115 mm
Dikte	8.5 mm
Materiaal	STAAL
Gewicht	345 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE