


Sluitring GS90135-IKO - GS90135-IKO

<https://www.123kogellager.nl/accessoires/ringen/sluitring/gs90135-iko>

IKO
THRUST BEARINGS

Thrust Roller Bearings



| Shaft dia. mm | Identification number | | | | | | | |
|------------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|--|
| | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g | |
| 90 | AZ 9013535 | 2 040 | AZK 9013514 | 750 | WS 90135 | GS 90135 | 645 | |

| Boundary dimensions mm | | | | | | | | | | Standard mounting dimensions mm | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ |
|---------------------------|-----|----|----------------|----------------|----------------|------|--------------------|----------------|----------------|------------------------------------|------------------------|-----------------------------------|---|---|
| d | D | T | d _c | D _c | D _w | B | r _s (1) | C ₁ | C ₂ | d _s Min. | D _s Max. | N | N | rpm |
| 90 | 135 | 35 | 90.05 | 134.5 | 14 | 10.5 | 1.1 | 100 | 129 | 128 | 101 | 181 000 | 626 000 | 2 500 |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3616060466945 |
| Binnendiameter | 90 mm |
| Buitendiameter | 135 mm |
| Dikte | 10.5 mm |
| Materiaal | STAAL |
| Gewicht | 645 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE