

SI Stangkop

DSIL5-T-K-DURBAL - DSIL5-T-K-DURBAL

https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/dsil5-t-k-durbal


DSIL5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Red end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄	
DSIL 5 T/K		5	M 5	8	6,00	18	8,5	11	

type	measurement [mm]			load rating C ₀ [N]	weight [g]	
	l ₂ min	W	h			
DSI / DSIL 5 T/K	10	9	27	13	6,0	0,016

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489070
Binnendiameter	5 mm
Buitendiameter	18 mm
Dikte	8 mm
Type	SI
Gewicht	16 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE