

SI Stangkop DSIL5-T-K-DURBAL - SIL5-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/sil5-t-k-durbal>


DSIL5-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	measurement (mm)						
DSIL 5 T/K	5	M 5	8	6,00	18	8,5	11		

type	measurement (mm)			h	d1	load rating C0 (N)	weight (kg)
	l1 min	W					
DSI / DSIL 5 T/K	10	9	27	13	6,0	0,016	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489070
Binnendiameter	5 mm
Buitendiameter	18 mm
Dikte	8 mm
Type	SI
Gewicht	16 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE