

SI Stangkop SIL14-T-K-DURBAL - SIL14-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/sil14-t-k-durbal>

SIL14-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	measurement [mm]					
SIL 14 T/K	14	M 14	19	13,50	36	20,0	25	

type	measurement [mm]			load rating C ₀ [N]	weight [kg]
	l ₁ min	W	h		
SI / SIL 14 T/K	25	22	57	16	0,160

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489339
Binnendiameter	14 mm
Buitendiameter	36 mm
Dikte	19 mm
Type	SI
Gewicht	160 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE