

SI Stangkop SI14-T-K-DURBAL - SI14-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si14-t-k-durbal>

SI14-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 14 TIK		14	M 14	19	13,50	36	20,0	25

type	measurement [mm]			h	d ₁ PT	load rating C ₁₀ [N]	weight [kg]
	l ₁ min	W					
SI / SIL 14 TIK	25	22	57	16	31,0	0,160	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489353
Binnendiameter	14 mm
Binnendiameter	0.551" inch
Buitendiameter	36 mm
Buitendiameter	1.417" inch
Dikte	19 mm
Dikte	0.748" inch
Type	SI
Gewicht	160 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE