

SI Stangkop

SIL22-T-K-DURBAL - SIL22-T-K-DURBAL

https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/sil22-t-k-durbal


SIL22-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Red end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄	
	SIL 22 T/K	22	M 22 x 1,5	28	20,00	54	30,0	38	

type	measurement [mm]			load rating C ₀ [N]	weight [kg]
	l ₃ min	W	h		
SI / SIL 22 T/K	37	32	84	15	68,0

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489575
Binnendiameter	22 mm
Buitendiameter	54 mm
Dikte	28 mm
Type	SI
Gewicht	540 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE