

## SI Stangkop SI28-T-K-DURBAL - SI28-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si28-t-k-durbal>


### SI28-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 28 TIK		28	M 27 x 2	35	24,00	66	37,0	46

type	measurement [mm]			d <sub>1</sub>	load rating C <sub>10</sub> [N]	weight [kg]
	l <sub>1</sub> min	W	h			
SI / SI128 TIK	51	41	103	15	107,0	0,820

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489681
Binnendiameter	28 mm
Buitendiameter	66 mm
Dikte	35 mm
Type	SI
Gewicht	820 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE