

## SI Stangkop SIL40-T-K-DURBAL - SIL40-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/sil40-t-k-durbal>


### SIL40-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race  
lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SIL 40 T/K			40	M 42 x 2	49	33,00	91	53,0	65

type	measurement (mm)				load rating C <sub>0</sub> (N)	weight (kg)
	l <sub>1</sub> min	W	h	d <sub>1</sub>		
SI / SIL 40 T/K	60	55	142	17		2,400

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489810
Binnendiameter	40 mm
Buitendiameter	91 mm
Dikte	49 mm
Type	SI
Gewicht	2400 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE