

## SA Stangkop DSAL6-T-K-DURBAL - DSAL6-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/dsal6-t-k-durbal>


### DSAL6-T-K



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
DSAL 6 T/K		6	M 6	9	6,75	20	

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
DSA / DSAL 6 T/K	21		36	13	7,7	0,020

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952489940
Binnendiameter	6 mm
Buitendiameter	20 mm
Dikte	9 mm
Type	SA
Gewicht	20 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE