

SI Stangkop DSSIL10-T-K-DURBAL - DSSIL10-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/dssil10-t-k-durbal>

DSSIL10-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 10 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			10	M 10	14	10,50	28	15,0	19	

type	l ₁ min	W	h	α	load rating C ₀ [kg]	weight [kg]
DSSIL / DSSIL 10 T/K	20	17	43	13	18,0	0,077

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952491172
Binnendiameter	10 mm
Binnendiameter	0.394" inch
Buitendiameter	28 mm
Buitendiameter	1.102" inch
Dikte	14 mm
Dikte	0.551" inch
Type	SI
Gewicht	77 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE