

## SI Stangkop SSIL25-T-K-DURBAL - SSIL25-T-K-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/ssil25-t-k-durbal>

### SSIL25-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSIL 25 T/K			d	G	B	C1	d1	d2	d3	d4
			25	M 24 x 2	31	22,00	60	33,5	42	

type	measurement [mm]				load rating C <sub>0</sub> [kg]	weight [g]
	l <sub>1</sub> min	W	h	α [°]		
SSI / SSIL 25 T/K	42	36	94	15	85,0	0,720

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952491646
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	60 mm
Buitendiameter	2.362" inch
Dikte	31 mm
Dikte	1.22" inch
Type	SI
Gewicht	720 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE