

SI Stangkop SI22-PK-DURBAL - SI22-PK-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si22-pk-durbal>

SI22-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

End end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	d	G	measurement (mm)			
right hand thread	h	C1	d1	d2	d3	
SI 22 PK	22	M 22 x 1,5	28	20,00	55	30,0 38

type	measurement (mm)				load rating C ₀ (kN)	weight (kg)
	l ₁ min	W	h	α [°]		
SI / SIL 22 PK	37	32	84	15	68,00	0,540

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952492247
Binnendiameter	22 mm
Buitendiameter	55 mm
Dikte	28 mm
Type	SI
Gewicht	540 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE