

SA Stangkop

SAL22-BK-DURBAL - SAL22-BK-DURBAL


<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sal22-bk-durbal>

SAL22-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C ₁	d ₂
SAL 22 BK	22	M 22 x 1,5	28	20,0	55

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
SA / SAL 22 BK	50	84	15	68,00	0,480

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952492698
Binnendiameter	22 mm
Buitendiameter	55 mm
Dikte	28 mm
Type	SA
Gewicht	480 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE