

SA Stangkop GAL15-UK-DURBAL - GAL15-UK-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/gal15-uk-durbal>


GAL15-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	measurement (mm)		
right hand thread			B	C ₁	d ₂
left hand thread					
GAL 15 UK	15	M 14	12	10,0	40

type	l, min	measurement [mm]	h	α [°]	load rating	weight
GAR / GAL 15 UK	34	20	63	8	C ₀ [kN]	[kg]
					36,0	0,140

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952492940
Binnendiameter	15 mm
Binnendiameter	0.591" inch
Buitendiameter	40 mm
Buitendiameter	1.575" inch
Dikte	12 mm
Dikte	0.472" inch
Type	SA
Gewicht	140 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE