

SA Stangkop GAL20-UK-2RS-DURBAL - GAL20-UK-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/gal20-uk-2rs-durbal>


GAL20-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)		measurement (mm)		load rating		weight
right hand thread	left hand thread	d	G	B	C1	C0 (kN)	(kg)
GAL 20 UK (-2RS)		20	M 20 x 1,5	16	13,0		53
type	l, min	measurement (mm) l, min	h	alpha [°]	load rating		weight
GAR / GAL 20 UK-2RS	43	27	78	9	60,0		0,310

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493091
Binnendiameter	20 mm
Buitendiameter	53 mm
Dikte	16 mm
Type	-
Gewicht	310 g
Draad	-
Smering	-
Verpakking	-
Standaard	-

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE