

# GE Stangkop GAR35-UK-2RS-DURBAL - DGAR35-UK-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/dgar35-uk-2rs-durbal>


## GAR35-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq 35$  with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq 17$  additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)					
GAR 35 UK-2RS	d	G	s	C <sub>1</sub>	d <sub>2</sub>	
	35	M 36 x 3	25	21,0	82	

type	measurement [mm]			load rating C <sub>0</sub> [kN]	weight [kg]
	l, min	h	a [°]		
GAR / GAL 35 UK-2RS	82	42	140	6	146,0

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3616060467621
Binnendiameter	35 mm
Buitendiameter	82 mm
Dikte	25 mm
Type	GE
Gewicht	1400 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1
Standaard	Geen standaard

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE