

## SI Stangkop GIL6-UK-DURBAL - GIL6-UK-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/gil6-uk-durbal>

### GIL6-UK



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number right hand thread	d		G	B	measurement [mm]		d <sub>2</sub>	d <sub>4</sub>
	6	M	6	6	4,4	21	10,0	13
GIL 6 UK								
type	measurement [mm]			α	load rating	weight		
GIR / GIL 6 UK	t <sub>3</sub> min	h	W	°	C <sub>0</sub> [kN]	[kg]		
	11	30	11	13	8,2	0,021		

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493589
Binnendiameter	6 mm
Buitendiameter	21 mm
Dikte	6 mm
Type	SI
Gewicht	21 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE