

## SI Stangkop GIL8-UK-DURBAL - GIL8-UK-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/gil8-uk-durbal>

### GIL8-UK



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number right hand thread	d		G		B		measurement [mm]			
	B	M	B	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	d <sub>4</sub>	h	W
GIL 8 UK	B	M	B	B	6,0	24	12,5	16		
type	measurement [mm]			$\alpha$ °	load rating C <sub>0</sub> [kN]	weight [kg]				
GIR / GIL 8 UK	l <sub>3</sub> min	h	W							
	15	36	14	15	12,9	0,039				

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493619
Binnendiameter	8 mm
Buitendiameter	24 mm
Dikte	8 mm
Type	SI
Gewicht	39 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE