

SI Stangkop DGIL20-UK-DURBAL - DGIL20-UK-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/dgil20-uk-durbal>

DGIL20-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	C ₁	d ₂	d ₄
DGIL 20 UK	20	M 20 x 1,5	16	13,0	53	27,5

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
DGIR / DGIL 20 UK	40	77	32	9	60,0	0,350

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493909
Binnendiameter	20 mm
Buitendiameter	53 mm
Dikte	16 mm
Type	SI
Gewicht	350 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE