

SI Stangkop GIR25-UK-2RS-DURBAL - GIR25-UK-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/gir25-uk-2rs-durbal>

GIR25-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	measurement [mm]						
right hand thread	d	G	B	C ₁	C ₂	d ₂	d ₄
GIR 25 UK (-2RS)	25	M 24 x 2	20	17,0	64	33,5	42

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GRL 25 UK	48	94	36	7	83,0	0,640

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493961
Binnendiameter	25 mm
Buitendiameter	64 mm
Dikte	20 mm
Type	SI
Gewicht	640 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE