

# SI Stangkop GIR30-UK-2RS-DURBAL - GIR30-UK-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/gir30-uk-2rs-durbal>

## GIR30-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]	
GIR 30 UK (-2RS)	d	G
	B	C <sub>1</sub>
	C <sub>2</sub>	d <sub>2</sub>
	d <sub>4</sub>	h
	W	

type	measurement [mm]			load rating	weight
	t <sub>3</sub> min	h	W	C <sub>0</sub> [kN]	[kg]
GIR / GIL 30 UK	56	110	41	110,0	0,930

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952494012
Binnendiameter	30 mm
Buitendiameter	73 mm
Dikte	22 mm
Type	SI
Gewicht	930 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE