

SI Stangkop GIL30-UK-2RS-DURBAL - GIL30-UK-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/gil30-uk-2rs-durbal>

GIL30-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	measurement [mm]			
right hand thread				C ₁	C ₂	d ₂	d ₄
GIL 30 UK (-2RS)	30	M 30 x 2	22	19,0	73	40,0	50

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 30 UK	56	110	41	6	110,0	0,930

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952494043
Binnendiameter	30 mm
Buitendiameter	73 mm
Dikte	22 mm
Type	SI
Gewicht	930 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE