

SA Stangkop POSL25-DURBAL - POSL25-DURBAL


<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/posl25-durbal>

POSL25



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required

order number	right hand thread		left hand thread		measurement [mm]		
	B	C ₁	G	M 24 x 2	B	C ₁	d ₁
POSL 25	25				31	22,00	60

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
POS / POSL 25	57	94	15	68,0	0,640

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952494784
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	60 mm
Buitendiameter	2.362" inch
Dikte	31 mm
Dikte	1.22" inch
Type	SA
Gewicht	640 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE