

SI Stangkop PHS30-DURBAL - PHS30-DURBAL


<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/phs30-durbal>

PHS30



female thread:
lubrication
required,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.



Rod end body:
surface chromium plated
Sliding combination:
steel / heavy duty bronze
Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated
Outer ring:
heavy duty bronze with lubrication
Lubrication:
lubrication required

| order number | right hand thread | left hand thread | d | G | B | C1 | d2 | d3 | d4 |
|--------------|-------------------|------------------|----|----------|----|-------|----|------|----|
| PHS 30 | | | 30 | M 30 x 2 | 37 | 25,00 | 70 | 40,0 | 50 |

| type | measurement [mm] | | | | load rating | weight |
|---------------|--------------------|----|-----|-------|---------------------|--------|
| PHS / PHSL 30 | I ₂ min | W | h | α [°] | C ₀ [kN] | [kg] |
| PHS / PHSL 30 | 51 | 41 | 110 | 17 | 88,0 | 1,100 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DURBAL |
| N° Ean13 | 3663952495538 |
| Binnendiameter | 30 mm |
| Buitendiameter | 70 mm |
| Dikte | 37 mm |
| Type | SI |
| Gewicht | 1100 g |
| Draad | Rechtse draad |
| Smering | zonder |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE