

SA Stangkop SAZPL6-S-DURBAL - SAZPL6-S-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sazpl6-s-durbal>


SAZPL6-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.



Rod end body:
surface zinc plated
Sliding combination:
steel / heavy duty bronze
Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated
Outer ring:
heavy duty bronze with lubrication
Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAZPL 6 S		6,35	1/4 - 28	9,53	7,14	19,05

type	inches	measurement [mm]		α	load rating	weight
		l ₁ min	h	[°]	C ₀ [kN]	[g]
SAZP / SAZPL 6 S	1 / 4 "	25,40	39,67	13	6,6	0,022

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952496023
Binnendiameter	6.35 mm
Binnendiameter	1/4" inch
Buitendiameter	19.05 mm
Buitendiameter	3/4" inch
Dikte	9.53 mm
Dikte	3/8" inch
Type	SA
Gewicht	22 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE