

SA Stangkop DSAZPL25-S-DURBAL - DSAZPL25-S-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/dsazpl25-s-durbal>


DSAZPL25-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated
Sliding combination:
steel / heavy duty bronze
Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated
Outer ring:
heavy duty bronze with lubrication
Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]	
right hand thread	left hand thread	d	G
DSAZPL 25 S		25,40	34,93

type	inches	measurement [mm]		load rating C ₀ [kN]	weight [kg]
		l ₁ min	h		
DSAZP / DSAZPL 25 S	1"	53,98	104,78	14	1,100

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952496320
Binnendiameter	25.4 mm
Buitendiameter	69.85 mm
Dikte	34.93 mm
Type	SA
Gewicht	1100 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE