

# SI Stangkop SIZJL6-DURBAL - SIZJL6-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/sizjl6-durbal>

## SIZJL6



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size 9 with grease nipple can be mounted upon  
request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number	right hand thread	left hand thread	measurement [mm]					
	d	B	C1	d2	G	d3	d4	
<b>SIZJL 6</b>	6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91	

  

type	inches	l <sub>1</sub> min	measurement [mm]		α	load rating	weight
			W	h	[°]	C <sub>0</sub> [kN]	[g]
<b>SIZJ / SIZJL 6</b>	<b>1 / 4 "</b>	15,88	9,53	33,32	13,5	9,6	0,023

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952496702
Binnendiameter	6.35 mm
Binnendiameter	1/4" inch
Buitendiameter	19.05 mm
Buitendiameter	3/4" inch
Dikte	9.53 mm
Dikte	3/8" inch
Type	SI
Gewicht	23 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE