

SI Stangkop

DSIZJ6-DURBAL - DSIZJ6-DURBAL


<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/dsizj6-durbal>

DSIZJ6



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number		measurement [mm]							
right hand thread	left hand thread	d	B	C ₁	d ₂	G	d ₃	d ₄	
DSIZJ 6		6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91	

type	inches	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	W	h				
DSIZJ / DSIZJL 6	1 / 4 "	15,88	9,53	33,32	13,5		9,6	0,023

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952496726
Binnendiameter	6.35 mm
Buitendiameter	19.05 mm
Dikte	9.53 mm
Type	SI
Gewicht	23 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE