

SI Stangkop

SIL17-ES-2RS-DURBAL - SIL17-ES-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/sil17-es-2rs-durbal>

SIL17-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number	right hand thread	left hand thread	measurement (mm)						
SIL 17 ES (-2RS)			d	G	B	C1	d2	d3	d4
			17	M 16	14	11,0	46	24,0	30

type	l ₁ min	measurement [mm]		h	α [°]	load rating C ₀ [kN]	weight [g]
SI / SIL 17 ES (-2RS)	34	27	67	10	45,0	0,22	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497020
Binnendiameter	17 mm
Binnendiameter	0.669" inch
Buitendiameter	46 mm
Buitendiameter	1.811" inch
Dikte	14 mm
Dikte	0.551" inch
Type	SI
Gewicht	220 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE