

SI Stangkop SI20-ES-2RS-DURBAL - SI20-ES-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si20-es-2rs-durbal>

SI20-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

Rod end body:
surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 20 ES (-2RS)		20	M 20 x 1.5	16	13,0	53	27,5	35

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SIL 20 ES (-2RS)	40	32	77	9	60,0	0,35

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497105
Binnendiameter	20 mm
Buitendiameter	53 mm
Dikte	16 mm
Type	SI
Gewicht	350 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE