

SI Stangkop SI30-ES-2RS-DURBAL - SI30-ES-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si30-es-2rs-durbal>

SI30-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number
right hand thread left hand thread

SI 30 ES (-2RS)	measurement [mm]		measurement [mm]			
	d	G	B	C ₁	d ₂	d ₄
	30	M 30 x 2	22	19,0	73	40,0

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	W	h			
SI / SII 30 ES (-2RS)	56	41	110	6	110,0	0,93

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497228
Binnendiameter	30 mm
Buitendiameter	73 mm
Dikte	22 mm
Type	SI
Gewicht	930 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE