

SI Stangkop SI30-ES-DURBAL - SI30-ES-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si30-es-durbal>

SI30-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
phosphated

Outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required



order number	measurement [mm]		measurement [mm]						
	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 30 ES			30	M 30 x 2	22	19,0	73	40,0	50

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h	α [°]		
SI / SII 30 ES	56	41	110	6	110,0	0,93

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497235
Binnendiameter	30 mm
Binnendiameter	1.181" inch
Buitendiameter	73 mm
Buitendiameter	2.874" inch
Dikte	22 mm
Dikte	0.866" inch
Type	SI
Gewicht	930 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE