

SI Stangkop

SI40-ES-2RS-DURBAL - SI40-ES-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si40-es-2rs-durbal>

SI40-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement (mm)									
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4	h	W	l1 min
SI 40 ES (-2RS)		40	M 39 x 3	28	23,0	92	52,0	65			

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SII 40 ES (-2RS)	65	55	142	7	180,0	2,0

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497389
Binnendiameter	40 mm
Binnendiameter	1.575" inch
Buitendiameter	92 mm
Buitendiameter	3.622" inch
Dikte	28 mm
Dikte	1.102" inch
Type	SI
Gewicht	2000 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE