

SI Stangkop SI60-ES-DURBAL - SI60-ES-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si60-es-durbal>

SI60-ES



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 60 ES		60	M 52 x 3	44	38,0	135	70,0	88

type	measurement [mm]				load rating C_0 [kN]	weight [kg]
	l_1 min	W	h	α [°]		
SI / SII 60 ES	70	75	175	6	450,0	5,5

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497662
Binnendiameter	60 mm
Buitendiameter	135 mm
Dikte	44 mm
Type	SI
Gewicht	5500 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE