

# SI Stangkop SI80-ES-2RS-DURBAL - SI80-ES-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/si80-es-2rs-durbal>


## SI80-ES-2RS



female thread;  
lubrication  
required,  
according to  
DIN ISO 12240-4;  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

Sliding combination:  
steel / steel  
Inner ring:  
bearing steel, hardened, ground and phosphated  
Outer ring:  
bearing steel, hardened, ground and phosphated  
Lubrication:  
lubrication required



order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 80 ES (-2RS)		80	M 64 x 4	55	47,0	180	95,0	110

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	W	h			
SI / SIL 80 ES (-2RS)	85	100	230	6	750,0	12,0

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497785
Binnendiameter	80 mm
Buitendiameter	180 mm
Dikte	55 mm
Type	SI
Gewicht	12000 g
Draad	Rechtse draad
Smering	met
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE