

## SA Stangkop SA12-E-DURBAL - SA12-E-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sa12-e-durbal>

### SA12-E



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 12 E		12	M 12	10	8,0	34

  

type	measurement [mm]			n	load rating	weight
	l <sub>1</sub> min	l <sub>2</sub>	h	[°]	C <sub>0</sub> [kN]	[kg]
SA / SA 12 E	28	17	54	11	24,5	0,085

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497990
Binnendiameter	12 mm
Binnendiameter	0.472" inch
Buitendiameter	34 mm
Buitendiameter	1.339" inch
Dikte	10 mm
Dikte	0.394" inch
Type	SA
Gewicht	86 g
Draad	Rechtse draad
Smering	met
Verpakking	-
Standaard	Geen standaard

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE