

SA Stangkop SA15-ES-2RS-DURBAL - SA15-ES-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sa15-es-2rs-durbal>

SA15-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 15 ES (-2RS)		15	M 14	12	10,0	40

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SA 15 ES (-2RS)	34	20	63		8	36,0	0,140

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952498034
Binnendiameter	15 mm
Binnendiameter	0.591" inch
Buitendiameter	40 mm
Buitendiameter	1.575" inch
Dikte	12 mm
Dikte	0.472" inch
Type	SA
Gewicht	140 g
Draad	Rechtse draad
Smering	met
Verpakking	-
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE