

# SA Stangkop

## SAL35-ES-2RS-DURBAL - SAL35-ES-2RS-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sal35-es-2rs-durbal>

### SAL35-ES-2RS



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
	<b>SAL 35 ES (-2RS)</b>	35	M 36 x 3	25	21,0	82	

type	measurement [mm]			n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h			
SA / SAL 35 ES (-2RS)	82	41	140	6	146,0	1,400

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952498423
Binnendiameter	35 mm
Buitendiameter	82 mm
Dikte	25 mm
Type	SA
Gewicht	1400 g
Draad	Linkse draad
Smering	met
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE