

SA Stangkop SA40-ES-DURBAL - SA40-ES-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sa40-es-durbal>

SA40-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



| order number | | measurement [mm] | | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|--|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | |
| SA 40 ES | | 40 | M 39 x 3 | 28 | 23,0 | 92 | |

| type | measurement [mm] | | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----------------|-----|--|----------|---------------------------------------|----------------|
| | l ₁ min | l ₂ | h | | | | |
| SA / SAL 40 ES | 86 | 46 | 150 | | 7 | 180,0 | 1,800 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DURBAL |
| N° Ean13 | 3663952498515 |
| Binnendiameter | 40 mm |
| Buitendiameter | 92 mm |
| Dikte | 28 mm |
| Type | SA |
| Gewicht | 1800 g |
| Draad | Rechtse draad |
| Smering | met |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE