

## SA Stangkop SAL70-ES-DURBAL - SAL70-ES-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sal70-es-durbal>

### SAL70-ES



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
	SAL 70 ES	70	M 56 x 4	49	42,0	160	

  

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SAL 70 ES	125	80	235	6	610,0	8,200	

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952498867
Binnendiameter	70 mm
Buitendiameter	160 mm
Dikte	49 mm
Type	SA
Gewicht	8200 g
Draad	Linkse draad
Smering	met
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE