

SA Stangkop
SAL80-ES-2RS-DURBAL - SAL80-ES-2RS-DURBAL

https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/sal80-es-2rs-durbal

SAL80-ES-2RS

male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
SAL 80 ES (-2RS)		80	M 64 x 4	55	47,0	180	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 80 ES (-2RS)	140	90	270		6	750,0	12,000

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952498904
Binnendiameter	80 mm
Buitendiameter	180 mm
Dikte	55 mm
Type	SA
Gewicht	12000 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE